

ZXR/C
SERIES

22-27 HP

ZERO TURN MOWERS



Power, Precision, Comfort



ZXR/ZXC SERIES

COMMERCIAL AND RESIDENTIAL ZERO TURN MOWERS

Whether you're cultivating a backyard haven or taming varied landscapes, our zero turn mowers deliver durable design, plush comfort, and uncompromising performance—empowering you to transform any terrain.

**WE DIG
DIRT**

- Hydro Gear® Transaxles
- Heavy Duty Chassis
- 22-27 HP
- Dual Plate 10-Gauge Steel Deck
- 7-Gauge at Deck Edge Area
- B&S, Kohler, and Kawasaki Engine Options
- 48", 54", & 60" Cutting Widths
- Large Fuel Capacity
- Ergonomic Controls
- Adjustable Suspension Seating
- Excellent Cut Quality



ZXR SERIES

PROVEN RESIDENTIAL PERFORMANCE: ZXR48, ZXR54 & ZXR60



Briggs & Stratton® Engine CXi 44T977

A 25 horsepower, 724cc V-twin engine built for turf applications. Featuring a 5-stage integrated cyclonic air cleaner, full-pressure lubrication with spin-on oil filter, Dura-Bore cast-iron sleeves, and electric start for reliable power in demanding conditions.



Kawasaki® Engine FT691V

A 22 horsepower, 726cc V-twin engine built for turf equipment. Features patented Vortical air filtration, cast-iron liners, pressurized lubrication, internally vented carburetor, and electric start for dependable power in demanding conditions.



Kohler® Engine Confidant ZT740

A 25 horsepower, 747cc V-twin engine from the Confidant series, designed for turf equipment. Features cast-iron cylinder liners, full-pressure lubrication with oil filter and cooler, heavy-duty air filtration, and electric start for dependable performance in demanding conditions.



Three Engine Options

The ZXR Series provides three engine choices, offering an optimal blend of power, durability, and efficiency for your specific needs. Engine options include B&S® CXi Series, Kawasaki® FT691V and Kohler® Confidant™.



Hydro-Gear Transaxles

ZT-3200 hydro-gear transaxles deliver smooth, responsive control and reliable power—built to handle tough mowing conditions with confidence and ease.



Dial Type Deck Adjustment

Ergonomically designed and easy to use, the dial allows precise control over cutting height for a clean, consistent finish.



Adjustable Suspension Seat

The plush 1.5" high-back suspension seat with adjustable settings enhances comfort, reduces fatigue, and delivers superior support on rough, uneven terrain.



Rear Guard

Durable steel rear guard protects key components and includes integrated tie-downs for convenience.



Heavy Duty Chassis

With its welded steel frame and heavy-duty components, the ZXR is built to withstand the demands of commercial mowing.



Heavy Gauge Fabricated Deck

Durable dual-plate 10-gauge fabricated deck, featuring a reinforced 7-gauge edge for enhanced strength and long-lasting performance.



LED Headlights

Bright, energy-efficient LED headlights ensure optimal visibility and safety, even during low-light conditions, for enhanced performance and precision.



Keyless Start

Easy-to-use push-button keyless start and integrated diagnostics panel provide quick, hassle-free engine ignition and real-time system monitoring for maximum convenience and uptime. An optional key kit is also available.



Multiple Cutting Widths

Choose between 48-, 54-, or 60-inch fabricated cutting decks to match your mowing needs—and choose the fit that works best for you.



ZXC SERIES

COMMERCIAL PRECISION: ZXC48, ZXC54 & ZXC60



Briggs & Stratton® Engine CXi 49T8

A 27 horsepower, 810cc V-twin engine designed for debris-heavy conditions. Features a patented 5-step cyclonic debris management system, full-pressure lubrication with spin-on filter, Dura-Bore cast-iron sleeves, and electric start for commercial reliability.



Kawasaki® Engine FT730V

A 24 horsepower, 726cc V-twin engine designed for commercial-grade performance. Featuring an internally vented carburetor with a fuel shut-off solenoid. With cast-iron liners, dual-element air filtration, pressurized lubrication and durable design, it's built for reliability in heavy-duty applications.



Kohler® Engine Command Pro® CV742

A 25 horsepower, 747cc V-twin engine from the Command PRO series, crafted for commercial turf equipment. Includes cast-iron cylinder liners, full-pressure lubrication with oil filter and integrated cooler, heavy-duty air filtration, and electric start for sustained reliability in tough conditions.



Three Engine Options

The ZXC Series is equipped with a selection of premium engines designed for commercial performance, reliability, and fuel efficiency. Choose from the B&S® CXi Series, Kawasaki® FT730V, or Kohler® Command Pro to meet the demands of your toughest mowing jobs.



Commercial Grade Transaxles

The ZXC Series is equipped with ZT-3400® transaxles, delivering high torque, faster ground speeds, and smooth, reliable control for tough commercial mowing.



Multiple Cutting Widths

Choose between 48-, 54-, or 60-inch fabricated cutting decks to match your mowing needs—and choose the fit that works best for you.



Premium Adjustable Suspension Seat

Standard 3-inch (76 mm) plush, high-back suspension seat is fully adjustable—delivering personalized comfort and support throughout the workday.



12.5 Gallon Fuel Capacity

The ZXC's large 12.5-gallon fuel tank supports extended mowing sessions, minimizing downtime and maximizing productivity on demanding commercial jobs.



Heavy Duty Chassis

Engineered with a welded steel frame and reinforced components, these commercial mowers are built to endure the rigors of tough, all-day mowing jobs.



Heavy Gauge Fabricated Steel Deck

Durable dual-plate 10-gauge fabricated deck, featuring a reinforced 7-gauge edge for enhanced strength and long-lasting performance.



Dial Type Deck Adjustment

Ergonomically designed and easy to use, the dial allows precise control over cutting height for a clean, consistent finish.



Keyless Start

Easy-to-use push-button keyless start and diagnostics panel come standard with a 12V charging adapter, offering quick startup and convenient power access to keep you working efficiently. An optional key kit is also available.



Anti-Scalp Ball Rollers

Front and rear anti-scalp ball rollers help protect your lawn by preventing the mower deck from digging in on uneven terrain for a smooth, even cut.



SPECIFICATIONS

MODEL		ZXR48	ZXR54	ZXR60	ZXC48	ZXC54	ZXC60		
Type		Premium Residential (Engine Choice with Each Deck Size)			Premium Commercial (Engine Choice with Each Deck Size)				
ENGINE		Briggs & Stratton®		Kohler®	Kawasaki®	Briggs & Stratton®		Kohler®	Kawasaki®
Type		CXi Series Engine 44T977		Confidant™ ZT740	FT691V	CXi Series Engine 49T8		Command Pro CV742	FT730V
Engine Gross	HP (kW)	25.0 (18.6)		25.0 (18.6)	22.0 (16.4)	27.0 (20.1)		25.0 (18.6)	24.0 (17.9)
Displacement	cu. in. (cc)	44.2 (724.0)		45.6 (747.0)	44.3 (726.0)	49.4 (810.0)		45.6 (747.0)	44.3 (726.0)
Choke		Manual Lever							
Fuel Tank Capacity	gal. (ℓ)	7.5 (28.4) 1 Tank: Left Side				12.5 (47.3) 2 Tanks: Left and Right Side			
Fuel Requirement		Unleaded Gasoline (87 Octane or higher)							
DRIVE TRAIN									
Model		Hydro-Gear ZT-3200				Hydro-Gear ZT-3400			
Displacement (Pump/Motor)	cc	10/16				12/16			
PTO TYPE									
Clutch	ft.-lb. (N-m)	125.0 (170.0)				200.0 (271.2)			
TIRE SIZE									
Front		13x5-6		13x6.5-6	13x6.5-6				
Rear		23x9.5-12			23x9.5-12	23x10.5-12			
TRAVELING SPEEDS									
Forward	mph (km/h)	9.0 (14.5)				10.0 (16.0)			
Parking Brake		Internal Integrated in Axle							
DIMENSIONS									
Overall Length	in. (mm)	80.7 (1,541.8)		81.7 (2,075.2)	80.7 (2,050.0)			81.7 (2,075.2)	
Overall Width (Chute Down)	in. (mm)	60.7 (1,541.8)	67.3 (1,709.4)	72.6 (1,844.0)	60.7 (1,541.8)		67.3 (1,709.4)		72.6 (1,844.0)
Overall Height (ROPS Upright)	in. (mm)	71.5 (1,816.1)							
Wheelbase	in. (mm)	48.5 (1,231.9)		49.5 (1,257.3)	48.5 (1,231.9)			49.5 (1,257.3)	
Width (Tire to Tire)	in. (mm)	50.3 (1,277.6)			50.3 (1,277.6)		51.3 (1,303.0)		
Approx. Curb Weight	lb. (kg)	1,033.0 (468.6)	1,052.0 (477.2)	1,075 (487.6)	1,033.0 (468.6)		1,052.0 (477.2)		1,075.0 (487.6)
MOWER DECK									
Mower Deck Type		Fabricated							
Lift Mechanism		Foot Pedal							
Deck Steel Thickness		Dual Plate 10-Gauge with 7-Gauge at Edge Area							
Anti-Scalp Ball Rollers		5 (4 front, 1 rear)	6 (4 front, 2 rear)	8 (4 front, 4 rear)	5 (4 front, 1 rear)		6 (4 front, 2 rear)		8 (4 front, 4 rear)
Cutting Width of Mower	in. (mm)	48.0 (1,219.2)	54.0 (1,371.6)	60.0 (1,524.0)	48.0 (1,219.2)		54.0 (1,371.6)		60.0 (1,524.0)
Blades		3 Notched (Optional Mulching)							
Cutting Height	in. (mm)	1.5-5 (38.1-127.0)							
Discharge Chute		Side (Molded Rubber)							
Deck Height Adjustment		Dial Type							
SEAT									
Suspension	in. (mm)	1.5 (38.1)				3.0 (76.2)			
Sliding Adjustment		Standard							
Arm Rest & Seat Belt		Standard							

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Hydro-Gear Transmission
- B&S®, Kohler®, or Kawasaki® Engines
- 10-Gauge Fabricated Steel Deck
- 7-Gauge at Edge Area
- Keyless Start
- Dial Type Deck Adjustment
- Adjustable Seat
- LED Lights
- Rear Guard
- Notched Blades
- Anti-Scalp Rollers
- Foldable ROPS
- Mulching Kit
- Hitch Kit
- Cup Holder

OPTIONAL EQUIPMENT

- Mulching Kit
- Headlamp Kit
- Work Lamp Kit
- Anti-Scalp Roller Kit (54" models only)



Daedong - USA, Inc.
KIOTI Tractor Division
6300 KIOTI Drive, Wendell, NC 27591 USA
Toll free 877-GO-KIOTI Fax 919-374-5001
Web www.KIOTI.com

Dealer Imprint Area