

ZXS
SERIES

24 HP

STAND-ON ZERO TURN MOWERS



Stand Tall. Cut Clean.






ZXS SERIES

CONQUER COMMERCIAL MOWING WITH POWER, SPEED AND PRECISION

ZXS stand-on zero turn mowers are built for landscapers who demand durability, efficiency, and control. Its rugged construction, high-performance engine, and smooth hydraulic controls let you fly through big jobs with pro-level cut quality. With a hydro-gear transmission, heavy gauge deck, adjustable dampers, and wide stance for balance on slopes, the ZXS is ready for tight schedules and tough terrain. Whether you're maintaining parks, campuses, or client properties, it delivers the speed, reliability, and comfort commercial pros count on—day in and day out.



**WE DIG
DIRT**

- Kawasaki FT730V Engine
- 24 HP
- Hydro Gear® ZT-3400 Transaxle
- Heavy Duty Chassis
- 10-Gauge Dual Plated Fabricated Steel Deck
- 7-Gauge Steel at the Edges
- 48" & 54" Cutting Widths
- Spring Suspension Operator Platform
- Intuitive Deck Lift



ZX5 SERIES

BUILT TO STAND ON. MADE TO DOMINATE.



Kawasaki® Engine FT730V

A 24 horsepower, 726cc V-twin engine designed for commercial-grade performance. Featuring an internally vented carburetor with a fuel shut-off solenoid. With cast-iron liners, dual-element air filtration, pressurized lubrication and durable design, it's built for reliability in heavy-duty applications.



Reinforced Mower Deck

Heavy-duty 10-gauge dual plated fabricated steel deck, reinforced with 7-gauge steel at the edges for lasting durability. Built to handle tough terrain while delivering a razor-sharp, professional-grade cut.




Ergonomic Controls

Intuitively positioned, the controls improve precision, reduce operator fatigue, and boost overall efficiency.





Spring Suspension Operator Platform

Spring suspension under the operator platform absorbs shocks and vibrations, delivering a smoother, more comfortable ride.



Intuitive Deck Lift

The hand lever deck lift with push-button transport release allows quick and easy cutting height adjustments.



Adjustable Controls

Dampers can be adjusted to optimize unit responsiveness, and the front reference bar can be customized to suit the operator's hand position and speed preferences.



Heavy Duty Chassis

From the welded steel frame to heavy-duty components, the ZXS is engineered for long-term use in tough environments.



Hydro-Gear ZT-3400 Transaxle

Delivers smooth, powerful, and precise control at your fingertips, letting you navigate tight turns and challenging terrain with effortless precision.



Anti-Scalp Rollers

Four front and two rear anti-scalp ball rollers help maintain an even cut by preventing the deck from digging into uneven terrain, protecting both the turf and mower deck during operation.



Excellent Cut Quality

Precision-engineered notched blades and a heavy-duty 10-gauge dual plated steel deck deliver a clean, even cut while reducing clumping for healthier turf.



Two Cutting Widths

Choose from two cutting widths—48" and 54"—to suit your mowing preferences, offering consistent performance and precision across a variety of turf conditions.



ZXS SERIES

PRECISION-ENGINEERED FOR COMFORT AND RELIABILITY



Notched Blades

Designed to enhance airflow, these blades provide a cleaner cut and help prevent clumping in thick or wet grass.



Kawasaki FT730V Engine

The 726cc commercial-grade V-Twin engine delivers serious mowing power. Advanced Vortical Air Filtration ensures cleaner operation, improved durability, and long-lasting performance in tough conditions.



Fast Travel Speeds

11 mph travel speeds let you cover more ground quickly, boosting productivity without sacrificing control or precision.



Large Fuel Tank

The 7-gallon fuel tank supports extended mowing sessions, reducing the need for refueling during long commercial jobs.



Spacious Center Console

The center tower, located behind the plush operator pad, offers ample space for easy maintenance and service access.



Convenient Drink Holder

Keep your drinks secure and within easy reach, so you can stay hydrated and focused while on the job.



Plush & Bolstered Operator Pad

Designed for comfort and stability, the plush, bolstered pad supports the operator through long hours of mowing on rough or uneven terrain.



Mulch Kit (Optional)

The optional mulch kit recycles clippings into natural mulch, reducing cleanup, returning nutrients to the soil, and enhancing performance with extra baffling for better distribution and an eco-friendly experience.



SPECIFICATIONS

MODEL	ZXS48		ZXS54
ENGINE			
Type	2-Cylinder, 90° V-Twin, Air-Cooled with Internally Vented Crankcase & Carburetor		
Engine Gross	HP (kW)	24.0 (17.9)	
Displacement	cu. in. (cc)	44.3 (726.0)	
Choke		Manual Lever	
Fuel Tank Capacity	gal. (ℓ)	7.0 (26.4)	
Fuel Requirement		Unleaded Gasoline (87 Octane or Higher)	
DRIVE TRAIN			
Model		Hydro-Gear ZT-3400	
Displacement Pump		12 cc / 16 cc	
TIRE SIZE			
Front		13x5-6	
Rear		23x10.5-12	
TRAVELING SPEEDS			
Forward	mph (km/h)	11.0 (17.7)	
Reverse	mph (km/h)	3.5 (5.6)	
DIMENSIONS			
Overall Length	in. (mm)	65.0 (1,650.0)	
Overall Width (Without Deck)	in. (mm)	60.6 (1,540.0)	68.5 (1,740.0)
Overall Height	in. (mm)	51.2 (1,300.0)	
Approximate Curb Weight	lb. (kg)	992.0 (450.0)	1,014.0 (460.0)
MOWER DECK			
Mower Deck Type		Fabricated	
Lift Mechanism		Hand Lever with Push Button Transport Release	
Deck Steel Thickness		10-Gauge Dual Plated Steel Deck with 7-Gauge at Edge Area	
Anti-Scalp Ball Rollers		6 (4 front, 2 rear)	
Cutting Width of Mower	in. (mm)	48.0 (1,219.0)	54.0 (1,371.6)
Blades		Notched	
Cutting Height	in. (mm)	1.5-4.5 (38.1-114.3)	
Discharge Chute		Molded Rubber	
Deck Height Adjustment		Pin	

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Kawasaki FT730V Engine
- Hydro-Gear ZT-3400 Transmission
- 48" (1,219 mm) & 54" (1,372 mm) Decks
- 7.0 Gallon (26.4 Liter) Fuel Capacity
- Spring Suspension Operator Platform
- Notched Blades
- Anti-Scalp Rollers
- Cup Holder

OPTIONAL EQUIPMENT

- Mulching Kit
- Anti-Scalp Roller Kit (54" models only)



Daedong - USA, Inc.
KIOTI Tractor Division
 6300 KIOTI Drive, Wendell, NC 27591 USA
Toll free 877-GO-KIOTI Fax 919-374-5001
Web www.KIOTI.com

Dealer Imprint Area