

# GKB DTA HIGH SPEED

**DELIVERS FASTER OPERATING SPEED WHILE  
MAINTAINING THE DEPTH AND PRECISION  
EXPECTED FROM DEEP TINE AERATION.**

The GKB DTA High Speed is specifically developed to relieve compaction quickly and efficiently, while minimizing surface disruption and downtime. The DTA HS combines GKB's proven deep tine aeration technology with a significantly increased working speed. The two-speed gearbox makes it easy to switch between deep aeration and fast, shallow operation, perfectly suited to today's time-critical maintenance schedules.

With three working widths available (48", 63", and 79"), the DTA HS can be matched precisely to the application – from greens and tees to fairways and sports fields. Front and rear rollers ensure stable operation and consistent results. The simple tine replacement system keeps setup and maintenance quick and straightforward, with 8 arms holding 2-18mm or 3-12mm solid or coring tines per arm.



**Contact Us:**

(888) 325-2532 | [sales@stecequipment.com](mailto:sales@stecequipment.com)

| Model             | DTA120HS   | DTA160HS   | DTA200HS   |
|-------------------|------------|------------|------------|
| Working Width     | 48"        | 63"        | 83"        |
| Weight            | 985 lbs    | 1205 lbs   | 1425 lbs   |
| Dimensions        | 48x51x48"  | 48x67x48"  | 48x83x4    |
| Power Requirement | 25 - 40 HP | 40 - 50 HP | 50 - 60 HP |

## Standard Features:

- Normal working depth of 0-10"
- Fast working depth of 0-4"
- Operating speed of 2.5 mph
- High-speed deep tine aeration with minimal surface disruption
- Two-speed gearbox for deep tine or high speed aeration
- Adjustable front and rear rollers
- Easy-to-replace tines
- Heavy-duty, maintenance-free sealed bearings
- Walterscheid PTO slip clutch
- Suitable for golf courses and sports fields
- Up to 25" of kick on tines

