

KIOTI CK2640 TRACTOR

GET THE JOB DONE RIGHT WITH A COMPACT TRACTOR BUILT FOR TOP PERFORMANCE.

The Kioti CK Series Compact Tractor is a reliable choice for anyone looking to take on various tasks across a 5-20 acre property. The CK Series is designed for homeowners, hobby farmers, and small-scale ranchers who need more power and performance from a compact tractor.

The Kioti CK2640 delivers 24.5 horsepower and a max 2,101 lb lift capacity with intelligent features, intuitive controls, and next-generation performance for your land.



Contact Us

(888) 325-2532 | sales@stecequipment.com

■ Eco-Friendly Diesel Engine

The whisper-quiet, eco-friendly Kioti Tier 4 CRDI engine improves fuel efficiency while reducing noise levels. Letting you conquer every task with quiet confidence.

■ Single Lever Joystick

The single lever joystick redefines front-loader operation. With a flick of your wrist, you command every movement, from raising the boom to lowering the bucket. A float position allows the bucket free flotation over the ground surface.

■ High Ground Clearance

The impressive 13.4" ground clearance lets you glide over rocks and uneven ground to conquer any terrain with confidence.

■ Powerful Hydrostatic Transmission

Hydrostatic transmission for effortless control, twin pedals for intuitive forward and reverse movements, seamlessly adjusting speed without ever touching a clutch. (Hydrostatic Models)

■ 3-Point Control Lever (Cab Models)

Allows you to raise and lower your implements with the slide of a lever with minimal effort yet maximum precision. Handily located lever eliminates the need for climbing and contorting, to attach or detach an implement.

■ Factory Installed Cab (Cab Models)

The deluxe factory-installed full size cab with air conditioning and heat lets operators perform tasks comfortably in any weather condition.



FULL SPECIFICATIONS



Tire Specs

Model	Agricultural	Industrial	R14	Turf
Front	13.6R-24	12.5-80-18	10-16.5	31-13.5-15
Rear	18.4R-34	18.4x24	320/85R24	44-18.0-20

Front End Loader Specs

Model	KL4040
Compatibility	Compatible with CK40 Series tractors
Weight	939.20 lb
Breakout Force at Pivot Pin	3,384 lb
Height Max in Carry Position	98.50 in
Bucket Capacity (Heaped)	10.20 ft ³
Rollback Angle Max	40 °
Reach at Max Height	17.40 in
Dump Angle Max	46 °
Digging Depth	5.1 in
Lift Height Max Pivot Pin	98.50 in
Lift Capacity to Full Height	1,835 lb
Reach at Ground	65 in

Backhoe Specs

Model	KB4075
Compatibility	Compatible with CK40 Series tractors
Digging Depth	83.40 in
Reach	126.40 in
Loading Height	75.60 in
Maximum Leveling Angle	11 °
Swing Arc	171 °
Transport Height	87.40 in
Transport Overhang	47.30 in
Bucket Rotation	177 °
Stabilizer Spread Down	86 in
Stabilizer Spread Up	46.40 in
Departure Angle	17 °
Weight	880 lb
Digging Force Bucket	2,817 lb
Digging Force Dipperstick	2,105 lb
Operating Pressure	2,466 psi





Model	CK2640	CK2640H	CK2640SEH	CK2640SEHC
Engine				
Engine	3A165LWM-U4		3A165LWH-U1	
Engine Manufacturer	KIOTI			
Power	24.50 hp			
Displacement	100.50 cu. in.			
RPM	2,400 rpm			
Fuel Type	Diesel			
Fuel Capacity	9 gal			
PTO	19.50 hp	18.7 hp	19 hp	18.8 hp
Transmission				
Transmission	Manual	Hydrostatic		
Speeds	9F x 3R	3-Range		
Travel Speeds Forward	0.8-10.6 mph	0-10.8 mph	0-10.8 mph	
Travel Speeds Reverse	1.0-6.9 mph	0-7.6 mph	0-7.6 mph	
Drive Train				
Brakes	Wet Disc Type			
Clutch	Dry Dual Stage	N/A		
Steering	Hydrostatic Power Steering			
PTO Type	Live		Independent	
Hydraulics				
Pump	Gear			
Pump Capacity	11.30 gpm	10.50 gpm	10.46 gpm	
Lift Capacity	1,631 lb		2,101 lb	
Hitch				
Type	Three Point			
Category	Category 1			
Control Type	Position			
Dimensions				
Length with Hitch	120.90 in			
Width	54.50 in			
Height	92.90 in			
Wheelbase	65.7 in			
Ground Clearance	13.40 in			
Turning Radius (with brake)	57.1 in		107.5 in	
Weight	2,634.50 lb	2,689.60 lb	2,921.1 lb	3,492.1 lb