

KIOTI CK4040 TRACTOR

GET THE JOB DONE RIGHT WITH A COMPACT TRACTOR BUILT FOR TOP PERFORMANCE.

The Kioti CK Series Compact Tractor is a reliable choice for anyone looking to take on various tasks across a 5-20 acre property. The CK Series is designed for homeowners, hobby farmers, and small-scale ranchers who need more power and performance from a compact tractor.

The Kioti CK4040 delivers 40 horsepower and a max 2,101 lb lift capacity with intelligent features, intuitive controls, and next-generation performance for your land.



Contact Us

(888) 325-2532 | sales@stecequipment.com

■ Eco-Friendly Diesel Engine

The whisper-quiet, eco-friendly Kioti Tier 4 CRDI engine improves fuel efficiency while reducing noise levels. Letting you conquer every task with quiet confidence.

■ Single Lever Joystick

The single lever joystick redefines front-loader operation. With a flick of your wrist, you command every movement, from raising the boom to lowering the bucket. A float position allows the bucket free flotation over the ground surface.

■ High Ground Clearance

The impressive 13.4" ground clearance lets you glide over rocks and uneven ground to conquer any terrain with confidence.

■ Powerful Hydrostatic Transmission

Hydrostatic transmission for effortless control, twin pedals for intuitive forward and reverse movements, seamlessly adjusting speed without ever touching a clutch. (Hydrostatic Models)

■ 3-Point Control Lever (Cab Models)

Allows you to raise and lower your implements with the slide of a lever with minimal effort yet maximum precision. Handily located lever eliminates the need for climbing and contorting, to attach or detach an implement.

■ Factory Installed Cab (Cab Models)

The deluxe factory-installed full size cab with air conditioning and heat lets operators perform tasks comfortably in any weather condition.



FULL SPECIFICATIONS



Tire Specs

Model	Agricultural	Industrial	R14	Turf
Front	13.6R-24	12.5-80-18	10-16.5	31-13.5-15
Rear	18.4R-34	18.4x24	320/85R24	44-18.0-20

Front End Loader Specs

Model	KL4040
Compatibility	Compatible with CK40 Series tractors
Weight	939.20 lb
Breakout Force at Pivot Pin	3,384 lb
Height Max in Carry Position	98.50 in
Bucket Capacity (Heaped)	10.20 ft ³
Rollback Angle Max	40 °
Reach at Max Height	17.40 in
Dump Angle Max	46 °
Digging Depth	5.08 in
Lift Height Max Pivot Pin	98.50 in
Lift Capacity to Full Height	1,835 lb
Reach at Ground	65 in

Backhoe Specs

Model	KB4075
Compatibility	Compatible with CK40 Series tractors
Digging Depth	83.40 in
Reach	126.40 in
Loading Height	75.60 in
Maximum Leveling Angle	11 °
Swing Arc	171 °
Transport Height	87.40 in
Transport Overhang	47.30 in
Bucket Rotation	177 °
Stabilizer Spread Down	86 in
Stabilizer Spread Up	46.40 in
Departure Angle	17 °
Weight	880 lb
Digging Force Bucket	2,817 lb
Digging Force Dipperstick	2,105 lb
Operating Pressure	2,466 psi



Model	CK4040	CK4040H	CK4040SE	CK4040SEH	CK4040SEHC
Engine					
Engine	3H-TM4A	3H-TH4A	3H-TM4B	3H-TH4B	
Engine Manufacturer	KIOTI				
Power	39.6 hp				
Displacement	111.40 cu. in.				
RPM / Aspiration	2,600 rpm				
Fuel Type	Diesel				
Fuel Capacity	9 gal				
PTO	35 hp	33.5 hp			
Transmission					
Transmission	Manual	Hydrostatic	Manual	Hydrostatic	
Speeds	9F x 3R	3-Range	12F x 12R	3-Range	
Travel Speeds Forward	1.0-15.5 mph	0-15.7 mph	1.1-16.4 mph	0-15.7 mph	
Travel Speeds Reverse	1.2-10.1 mph	0-11 mph	1.1-16 mph	0-11 mph	
Drive Train					
Brakes	Wet Disc Type				
Clutch	Dry Dual Stage	N/A			
Steering	Hydrostatic Power Steering				
PTO Type	Live		Independent		
Hydraulics					
Pump	Gear				
Pump Capacity	11.30 gpm				
Lift Capacity	1,631 lb		2,101 lb		
Hitch					
Type	Three Point				
Category	Category 1				
Control Type	Position				
Dimensions					
Length with Hitch	120.90 in				
Width	54.50 in				
Height	92.90 in				
Ground Clearance	13.40 in				
Turning Radius (with brake)	57.1 in		107.5 in		
Weight	2,678.6 lb	2,733.70 lb	3,038 lb	2,921.1 lb	3,509.8 lb