

VGR TOPCHANGER

XP Wetject

**DESIGNED TO IMPROVE SOIL CONDITIONS,
PROMOTE HEALTHIER TURF, AND HELP GET
MORE OUT OF EVERY PASS.**

The TopChanger XP is an aeration machine that works on the basis of water and high pressure. Water is used under high pressure to blast holes into the soil. Water aeration opens up possibilities for injecting sand, with soil-improving products if desired, into the soil. Using water for aeration, especially in soils containing rocks, helps minimize any chance of machine breakdowns.

The TopChanger injects sand deep into the soil, keeping any residue left on the surface to a minimum. The sand helps the water better infiltrate into the soil profile. This unique aeration method ensures lower operational costs and firmer and well aerated turf.



Contact Us:

(888) 325-2532 | sales@stecequipment.com

Model	Topchanger XP
HP	45 hp (+ creep or hydrostatic)
Dimensions	36.3 x 71.6 x 36.7 in
Working Width	63 in
Weight	1500 lbs (empty) / 2000 lbs (fully loaded)
Hopper Capacity	500 lbs
PTO Requirement	540 rpm

Standard Features:

- Working Speed of 0.3 - .5 m/hr
- Minimum Water Flow of 16 gpm
- The soil can be filled with wet or dry sand
- Improved hopper design to help reduce spilling sand when loading
- Improved software to reduce water usage
- LED display and Touchscreen
- Simplified operation. Rear mounted hose to aid turning
- Integral tool box to hold maintenance tools.
- Wire roller scrapers front and back to help surface cleanliness.
- Tool kit and spare parts package included
- Training and setup options available

